



Article

Material Flow Analysis-Based Sustainability Assessment for Circular Economy Scenarios of Urban Building Stock of Vienna

Jakob Lederer * o and Dominik Blasenbauer

Institute for Chemical, Environmental, and Bioscience Engineering, TU Wien, 1060 Vienna, Austria; dominik.blasenbauer@tuwien.ac.at

* Correspondence: jakob.lederer@tuwien.ac.at; Tel.: +43-158801166155

Abstract: Urban buildings consume raw material and energy, and they produce waste and greenhouse gasses. Sustainable urban development strategies aim to reduce these. Using the case study of buildings in Vienna, this article evaluates the impact of a defined urban development pathway on the heating energy demand, greenhouse gas emissions, and total material requirement of buildings in Vienna for 2021-2050. Furthermore, the impact of recycling to reduce the total material requirement and to increase the circular material use rate is evaluated. The results show that the heating energy demand can be reduced to meet the targets of Vienna's sustainable development strategy. The same does not count for greenhouse gas emissions. To meet the targets for the latter, the renovation of old buildings by thermal insulation should be expanded and heating systems substituted. With respect to the total material requirement, the recycling of demolition waste from buildings in Vienna to produce secondary raw materials for buildings in Vienna can help to achieve the reduction targets of Vienna's sustainable development strategy so that in the year 2050, the material footprint is only 44% of the value of the year 2019. Since there is a contradiction between the total material requirement and the circular material use rate, the latter has to be discussed for its use as a circular economy indicator, since the aim of circular economy is not to produce as much recycling materials as possible, but to reduce resource consumption to a sustainable level.

Keywords: buildings; circular economy; material footprint; demolition waste; circular material use rate; heating energy demand; greenhouse gas emissions

1. Introduction

Human history is characterized by a number of groundbreaking transformations. One of the most recent, but also most dramatic, is urbanization. Today, 55% of the global population lives in cities. It is projected that by the year 2050, this share will increase to 68% [1]. One consequence of this rapid growth is that cities not only became important consumers of energy and raw materials, but also large producers of emissions and waste [2,3]. In order to reduce the negative consequences associated with this urban consumption and waste generation, many cities defined strategies, subsumed under the term sustainable urban development [4,5]. While most of these strategies aim to reduce energy consumption and greenhouse gas (GHG) emissions, others also foresee a reduction in the consumption of primary raw materials [6,7]. In order to achieve these reductions, two of the most important sectors in urban societies that have to be targeted are the transport sector and the building construction sector [8–15]. This also accounts for the Austrian capital of Vienna, where recent studies show that from the two sectors, building construction is twice as relevant for the resource consumption of construction materials than the transport sector [16–20].

When it comes to the measures needed to achieve a reduction in the consumption of construction materials in the building construction sector, cities like Amsterdam [5,7], Leuven [6], and Porto [21] focus on enhanced recycling or reuse of materials from the demolition of buildings in order to produce goods or secondary raw materials that can



Citation: Lederer, J.; Blasenbauer, D. Material Flow Analysis-Based Sustainability Assessment for Circular Economy Scenarios of Urban Building Stock of Vienna. *Sustainability* **2024**, *16*, 7319. https://doi.org/10.3390/su16177319

Academic Editor: Francesco Asdrubali

Received: 28 July 2024 Revised: 13 August 2024 Accepted: 20 August 2024 Published: 26 August 2024



Copyright: © 2024 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

substitute primary raw materials for new constructions. These measures, which are a part of a circular economy, are also important pillars of the sustainable urban development strategy of Vienna [22]. However, in addition, this strategy, which is called the Smart Climate City Strategy Vienna [22], also aims to reduce resource consumption in the buildings sector by means of demolishing fewer buildings. In this sense, the Smart Climate City Strategy Vienna offers a broader concept of sustainability for the building sector [23]. In order to evaluate and monitor the success of different measures to achieve a sustainable urban development in Vienna, the Smart Climate City Strategy Vienna uses a number of indicators. With respect to resource consumption, the most important indicator is the consumptionbased material footprint, which was defined for Vienna as the total material requirement (TMR) [24,25]. In Vienna, this TMR should be reduced in all sectors by -30% until the year 2030, -40% until the year 2040, and -50% until the year 2050. The reduction targets are in comparison to the base year for the TMR, which is the year 2019 [22]. Next to the TMR, the final energy consumption should also be reduced. For buildings in Vienna, the heating energy demand (HED) is particularly mentioned of relevance [26]. The first reason for this is that the HED is the largest consumer of energy in buildings, much larger than the energy demand for warm water or electricity. The second reason is that the HED is also associated with higher GHG emissions than other energy uses, since the HED is provided in Vienna mainly by district heating and decentral floor heating by boilers, both of which are fueled to a large extent by natural gas [26]. Other energy demands for light, power, and cooling are quantitatively not only less important than heating, but they also rely less on fossil fuels and thus generate much less GHG emissions. The reason for that is that these energy demands are covered by electricity, and more than 80% of the electricity produced and consumed in Austria comes from renewable energy sources. Moreover, in summertime, when the demand for cooling for instance has had its peak, more than 100% of the electricity produced in Austria comes from renewable energy sources, allowing not only for covering of the increasing demand of electricity in Austria, but also for exporting of a substantial surplus to neighbouring countries [27]. Coming back to the HED and its reduction, the reduction targets for the energy consumption of buildings in Vienna are -20% until the year 2030 and -30% until the year 2040 [22]. Furthermore, according to the Smart Climate City Strategy Vienna, the direct GHG emissions should also be reduced in Vienna. The reduction targets are -55% until the year 2030 and -100% until the year 2040. This GHG reduction does not include embodied or indirect GHG emissions. All of these reduction targets, the TMR, the HED, and the GHG, are measured on a per-capita basis. The base for the HED and the GWP reductions is the average annual value of the timespan 2005-2010. As aforementioned, for the TMR, the base is the annual value of the year 2019 [22]. Besides the Smart Climate City Strategy Vienna, other regulations relevant to assessing the sustainable development of the city exist. At a national level, the Austrian Circular Economy Strategy not only aims to reduce the material footprint but also to increase the Circular Material Use Rate (CMUR) from 12% in the year 2020 to 18% in the year 2030. Hosting more than a fifth of the population of the country, Vienna will play a crucial role to fulfil this national target. With respect to the energy demand scenarios for Austria, the most important source comes from the Umweltbundesamt, which is the Federal Environment Management Agency of Austria [28]. This document, which is also one of the scientific bases for the Austrian National Energy and Climate Plan [29] in the German Nationaler Energie- und Klimaplan (NEKP), models three scenarios for energy demand in the buildings sector until the year 2050 in Austria. The first scenario is the "With Existing Measures" or WEM scenario, the second is the "With Additional Measures" or WAM scenario, and the third is the Transition scenario. Having a look at the building sector in these scenarios, it becomes clear that the energy demand reduction targets of Vienna are much higher than those modelled in the scenarios. In particular, the WEM scenario models the energy consumption reduction per capita until 2030 by -10%, until 2040 by -13%, and until 2050 by -14%. The WAM scenario models a reduction of -15% (2030), -23% (2040), and -27% (2050), while the Transition scenario models a reduction of -19% (2030), -34%

Sustainability **2024**, 16, 7319 3 of 26

(2040), and -42% (2050) [28]. In comparison, the energy reduction targets for Vienna are -20% (2030) and -30% (2040) and thus comparable to the Transition scenario modelled by the *Umweltbundesamt*.

With respect to achieving the sustainable urban development targets for buildings in Vienna, there are a number of recent studies investigating scenarios that aim to analyze possible future urban development pathways in the context of the Smart Climate City Strategy Vienna. A recent study by Lederer et al. [30] for instance calculated the direct material requirement (DMR) of the most important construction minerals under an enhanced circularity scenario, suggesting that re-use and recycling can contribute, but will not be sufficient alone, to meeting Vienna's resource consumption reduction target. This study, however, used the material flow data of construction materials and demolition waste from the year 2014, but not future scenarios or development pathways for material consumption and waste generation. Such scenarios were developed by Lederer et al. [17], who found that a massive reduction in the demolition of old buildings in combination with enhanced renovation, the so-called RENO-scenario in their study, is favourable with respect to reducing the material consumption if compared to a continuation of the business-as-usual, the so-called BAU-scenario, or the DEMO-scenario, which foresees more demolition of old buildings that can then be substituted by new low-energy buildings. Moreover, using the model of Lederer et al. [17], Haas et al. [31] found that the RENO-scenario outperforms the other scenarios with respect to savings of heating energy and mitigation of greenhouse gas emissions. Yet, there are certain points that must be considered and discussed with respect to these studies. First, the model of Lederer et al. [17] modelled material inputs and outputs in the building sector of Vienna in the future until the year 2050. However, the study did not consider to which extent recycling of the material outputs can reduce the material inputs and thus contribute to sustainable development in Vienna. To do so, a combination of the material flow scenarios from Lederer et al. [17] with recycling scenarios from Lederer et al. [30], would be inevitable. Second, the scenario-based model of Lederer et al. [17] started its calculation in the year 2016. This means that now, in the year 2024, there is already statistical data available for the years 2016-2020. These data can first of all be used to update the material flow model of Lederer et al. [17], which can be combined with the recycling scenarios from Lederer et al. [30]. Furthermore, it can serve to update the HED and GHG emissions model from Haas et al. [31]. Finally, and probably most importantly, the new statistical data can also be used to indicate the most likely scenario as a future development pathway of the building stock in Vienna.

Against this background, this study investigates the following research questions.

- (1) What is the annual material input and output, the heating energy demand, and the direct greenhouse gas emissions from the heating of buildings in Vienna for a defined development pathway of the building sector in the city and the timespan 2021–2050?
- (2) What are the material flows (inputs and outputs) of the most important construction materials and demolition waste of buildings in Vienna in the timespan 2021–2050, considering both enhanced vs non-enhanced domestic circular economy within the building sector with demolition waste from the city for secondary raw materials for the city?
- (3) To which extent can recycling reduce the consumption-based material footprint and at the same time increase the circular material use rate of buildings in Vienna if domestic recycling in the building sector is further encouraged?

2. Materials and Methods

2.1. An Updated Model for Material Flows, Heating Energy Demand, and Greenhouse Gas Emissions of Vienna's Building Stock

The model from Lederer et al. [17] basically consists of material intensity coefficients (MICs) in mass per reference values, in the present case kg/m² net floor area (NFA), and reference values (RVs) of different building types, in the present case given in m² NFA. Both are used to model material flows of inputs and outputs, but also for other parameters, like

Sustainability **2024**, 16, 7319 4 of 26

HED or GHG emissions. While the MICs are not changed in the model, the RVs are, since these are affected by the developments observed in the years 2016–2020.

Thus, as a first step, statistical data for the years 2016–2020 were retrieved. These data, which referred to the NFA of new constructed buildings, thermal renovation on existing buildings, attic extensions on existing buildings, and demolition of existing buildings, the latter based on demolition waste statistics, were then used twofold, namely first for defining a likely development pathway for Vienna's buildings stock 2021–2050, and secondly for updating the material input and output model from Lederer et al. [17] with new data. These applications are discussed here in detail before we present how these updated data sets can be used to model material flows, heating energy demand, and greenhouse gas emissions of the development pathway defined.

2.1.1. Definition of a Development Pathway for Vienna's Building Stock 2021–2050

Based on this statistical data for the years 2016–2020, Vienna more likely develops its building stock somewhere in between the aforementioned BAU-scenario and the DEMO-scenario from Lederer et al. [17]. For instance, the amount of waste generated from buildings has increased since 2016, as shown in Figure 1, while the NFA of buildings being renovated by thermal insulation remains virtually constant, as shown in Figure 2. For this study, it was thus assumed that Vienna would start in the year 2021, with the assumptions as defined in the DEMO-scenario of Lederer et al. [17]. Furthermore, it was assumed that the buildings stock of the city is gradually managed as in the BAU-scenario, which means a reduction in the number of buildings demolished but an increase in the number of buildings thermally renovated, if compared to the DEMO-scenario.




Figure 1. Generation of concrete and debris (bricks, mortar, etc.) demolition waste from buildings generated in Vienna based on statistics from the City of Vienna [32] if compared to the amounts modelled in the scenarios by Lederer et al. [17].

2.1.2. Updated Material Input and Output Model by New Data

After having selected the future development pathway for buildings in Vienna until the year 2050, the model used to calculate net floor areas (NFAs) and material inputs and outputs of the building stock from Lederer et al. [17] was updated by recently published statistical data on the new construction of buildings, new attic extensions on existing buildings, new thermal insulation on existing buildings, and demolition of existing buildings. The data sources for these data sets come from national and city statistical departments [32–34]. These updated data from statistics, as well as the new modelled data based on these statistics, are shown in NFAs in Table 1 as well as in Tables S1–S4 in the Supplementary File.

Sustainability **2024**, 16, 7319 5 of 26




Figure 2. NFA of residential buildings renovated by thermal insulation based on statistics [32] compared to the amounts modelled in the scenarios by Lederer et al. [17].

Table 1. Updated statistical data of NFA in m² for the years 2016–2020, and new modelled data based on these updates for the years 2021, 2030, 2040, and 2050 for buildings in Vienna. Building categories according to their use (Residential, Service, etc.).

Year	2016	2017	2018	2019	2020	2021 (1)	2030 (2)	2040 (2)	2050 (3)
		Update	d Data from	Statistic		1	Modelled Da	led Data Updated	
Population (capita)	1,855,25	54 1,870,282	1,885,310	1,900,338	1,915,366	1,930,394	2,065,647	2,195,061	2,286,094
New construction of re	esidential, serv	ice, industrial	, and other	buildings ⁽⁴⁾)				
Residential	544,960	656,256	808,960	851,712	897,088	523,841	506,241	486,685	467,130
Service	375,271	375,271	375,271	375,271	375,271	428,612	412,075	393,700	375,325
Industrial	70,630	70,630	70,630	70,630	70,630	211,176	192,196	171,106	150,016
Other	444,714	444,714	444,714	444,714	444,714	250,752	248,323	245,623	242,924
New attic extension or	n existing build	ings (only ap	plicable to r	esidential b	uildings) ⁽⁴⁾				
Residential	294,600		392,800	441,900	294,600	176,405	176,405	176,405	176,405
1800-	1918 235,680	274,960	314,240	353,520	235,680	124,656	124,656	124,656	124,656
1919-	1945 58,920	68,740	78,560	88,380	58,920	51,749	51,749	51,749	51,749
New thermal insulation	n on existing b	uildings (only	y applicable	to residenti	ial and servi	ice building	(s) ⁽⁴⁾		
Residential	369,475		197,476	260,073	392,999	174,847	305,541	450,756	595,970
1800-	1918 66,504		33,211	50,875	38,095	33,211	74,597	120,581	166,565
1919-	1945 93,773	53,968	37,932	44,933	177,533	15,303	38,729	64,757	90,785
1946-	1980 209,198	3 207,163	126,333	164,265	177,371	126,333	192,215	265,418	338,620
Service	137,159	136,640	135,856	135,260	134,563	134,563	137,054	139,823	142,592
1800-	1918 85,655	85,489	85,238	85,047	84,824	84,824	85,681	86,634	87,587
1919-	1945 8194	8150	8084	8033	7974	7974	8192	8434	8676
1946-		43,001	42,534	42,180	41,765	41,765	43,181	44,755	46,329
Demolition of existing	buildings (4)								
Residential	113,478	3 171,523	130,311	152,511	148,199	175,731	158,132	138,576	119,022
1800-	1918 79,809	120,632	91,648	107,261	93,610	120,632	108,907	95,880	82,853
1919-	1945 27,236	41,168	31,276	36,605	44,160	44,160	39,357	34,019	28,682
1946-	1980 5521	8345	6340	7420	8951	8951	7978	6896	5814
1981-	2000 912	1378	1047	1225	1478	1478	1380	1271	1163
2001-	2020 -	-	-	-	-	510	510	510	510
Service	98,644	149,101	113,277	132,576	159,941	160,451	137,054	111,058	85,060
1800-	,	,	19,090	22,342	26,953	26,953	23,925	20,560	17,195
1919–	1945 4400	6651	5053	5914	7135	7135	6243	5253	4262
1946-	1980 30,876	46,669	35,456	41,497	50,062	50,062	42,678	34,473	26,267
1981-	2000 46,744	70,654	53,678	62,823	75,791	75 <i>,</i> 791	63,856	50,596	37,336
2001-	2020 -	-	-	-	-	510	352	176	-

Sustainability **2024**, 16, 7319 6 of 26

Ye	ear	2016	2017	2018	2019	2020	2021 (1)	2030 (2)	2040 (2)	2050 (3)
Industrial		82,400	124,547	94,623	110,742	133,602	133,602	114,621	93,531	72,441
	1800-1918	10,287	15,549	11,813	13,825	16,679	16,679	14,726	12,556	10,385
	1919-1945	9447	14,278	10,848	12,696	15,317	15,317	13,410	11,291	9173
	1946-1980	40,725	61,556	46,766	54,733	66,031	66,031	56,413	45,727	35,040
	1981-2000	21,941	33,164	25,196	29,488	35,575	35,575	30,072	23,957	17,843
	2001-2020	_	-	-	_	-	-	-	-	-

Table 1. Cont.

2.1.3. Modelling the Material Input and Output of the Updated Building Model of Vienna

By combining the data for the RVs (Table 1) by material intensity coefficients (MICs), the material flows MF were modelled after Equation (1):

$$MF_{m,t} = \sum_{i,j,r=1}^{i,j,r=p} MIC_{flow,m,i,j,r} \times RV_{flow,t,i,j,r}$$
(1)

in which $MF_{m,t}$ is the material flow for the material m in the year t in kg/year, and $MIC_{flow,m,i,j,r}$ is the material intensity coefficient of material m for buildings distinguishing between age category i, use category j, and renovation status r, given in kg/m² NFA. These units also indicate the reference value $RV_{flow,t,i,j,r}$ for different building types, which is m² NFA. For the MICs, data from Lederer et al. [17] were used (Table 3 of their article, Table A1, and S5 in this article). The RV came from the updated model (see Table 1 and Supplementary File spreadsheets "S1 Res-NFA", "S2 Ser-NFA", "S3 Ind-NFA", "S4 Oth-NFA").

2.1.4. Modelling the Heating Energy Demand of the Updated Building Model of Vienna

The updated RVs from Table 1 can also be used to determine the HED for the building stock in Vienna. For residential and service buildings, energy for floor heating is the most relevant energy consumption. The same cannot be said for other buildings where the HED is less relevant [26]. In addition, and as aforementioned, the energy consumption for other purposes is less relevant. In order to model the HED of these building types, first the gross floor area (GFA) had to be determined, since standard values for the HED are usually given in [kWh/m² GFA]. In the model of Lederer et al. [17]., the development of the building stock was given in m² net floor area conditioned ($NFA_{conditioned,i,j,r}$) for residential buildings and m³ gross volume ($GV_{i,j,r}$) for service buildings. The indices indicate the age category i, use category j, and renovation status r of buildings. Both data can be found in Lederer et al. [17]. For the reference values, Lederer et al. [35] provided conversion factors $CF_{i,j,r}$ in order to convert from $NFA_{i,j,r}$ to $GFA_{i,j,r}$ (see Equation (2)).

$$GFA_{i,j,r} = NFA_{i,j,r} \times CF_{i,j,r} \tag{2}$$

The data for the NFA are in Table 1. The $CF_{i,j,r}$ data came from analyzing 256 buildings of different ages, sizes, and uses in Vienna [35]. The $CF_{i,j,r}$ values are shown in Table 2.

After converting the RVs of the building stock into m^2 GFA, the floor HED for the timespan 1991–2050 were modelled. This was performed by multiplying the specific floor HED of each building class by the reference value. The total floor heating energy demand HED_{total} per year, given in [kwh/yr], was calculated, as shown in Equation (3).

$$HED_{total} = \sum_{i,j,r=1}^{i,j,r=p} HED_{GFA,i,j,r} \times RV_{i,j,r}$$
(3)

⁽¹⁾ Modelled data for the DEMO-scenario, based on updated statistics for 2016–2020. ⁽²⁾ Linear interpolation between DEMO-scenario 2021 and BAU-Scenario 2050. ⁽³⁾ Modelled data for the BAU-scenario, based on updated statistics for 2016–2020. ⁽⁴⁾ Building construction statistics from Statistics Austria [33], thermal renovation statistics from the City of Vienna [34], and demolition waste statistics from the City of Vienna [32].

where $HED_{GFA,i,j,r}$ is the heating energy demand of each building type per m² GFA in [kwh/m² GFA/yr] and $RV_{i,j,r}$ is the reference value, both distinguishing between age category i, use category j, and renovation status r. The $RV_{i,j,r}$ is given in [m² GFA] and can be found in the Supplementary File spreadsheets ("S1 Res-NFA", "S2 Ser-NFA", "S3 Ind-NFA", "S4 Oth-NFA"). Values for $HED_{GFA,i,j,r}$ are shown in Table 2 and the Supplementary File spreadsheet (Table "S7 Heating-energy data" and "S8 Heating-energy-carrier").

Table 2. Updated statistical data for the years 2016–2020, and new modelled data based on these updates for the years 2021, 2030, 2040, and 2050 for buildings in Vienna.

Building Type	1800-1918	1919–1945	1946–1980	1981–2000	2001–2020	2021–2050				
	Cor	version factor	CF _{GFA/NFA} [-	·] ⁽¹⁾						
Residential	0.76	0.81	0.83	0.81	0.80	0.80				
Service	0.75	0.77	0.90	0.95	0.95	0.95				
Heating energy demand [kwh/m² GFA]										
Residential										
Existing buildings	100 ⁽²⁾	90 ⁽²⁾	80 (2)	50 ⁽²⁾	45 ⁽³⁾	22 (4)				
Thermal insulation	38 ⁽⁵⁾	38 ⁽⁵⁾	38 ⁽⁵⁾							
Attic extension	38 (5)	38 (5)								
Service										
Existing buildings	250 ⁽⁶⁾	250 ⁽⁶⁾	250 ⁽⁶⁾	130 ⁽⁶⁾	70 ⁽⁶⁾	22 (6)				
Thermal insulation	80 (6)	80 (6)	80 (6)							
	Heatir	ng energy dem	nand [kwh/m²	NFA]						
Residential		0 0,	_	_						
Existing buildings	132	111	96	62	56	28				
Thermal insulation	50	47	46							
Attic extension	50	47								
Service										
Existing buildings	333	325	272	144	74	23				
Thermal insulation	107	104	87							

⁽¹⁾ Lederer et al. [35]; (2) Müller [36]; (3) OIB [37]; (4) OIB [37]; (5) Stadt Wien [38]; (6) Bayer et al. [39].

2.1.5. Modelling the Greenhouse Gas Emissions of the Updated Building Model of Vienna

After determining the HED, it is possible to calculate the direct GHG emissions. Note that in contrast to Haas et al. [31], indirect and embodied GHG emissions are not considered, which is in line with the Smart Climate City Strategy Vienna [22]. The corresponding indicators are the GHGs for supplying the buildings with different energy carriers for heating k. According to the Smart Climate City Strategy Vienna, only these direct GHGs are to be considered, while the GHGs associated with the provision of materials are not. The calculation was performed as in Equation (4):

$$GHG_{direct, heating} = \sum_{k=1}^{k=1} HED_k \times EF_{GWP,k}$$
 (4)

where $GHG_{direct,\ heating}$ is the greenhouse gas emissions in kg $CO_{2\text{-equivalent}}$ from the heating energy demand of different energy carriers for heating HED_k multiplied by the emission factors of all of these energy carriers $EF_{GWP,k}$. The data for the distribution of the total heating energy demand HED_{total} to the energy carriers k came from Veigl et al. [26], who modelled one heating energy consumption pathway for Vienna until the year 2050. Even though Veigl et al. did not consider recent ambitions to achieve carbon neutrality until 2040, the results give an impression of the additional steps required. Using these data, the HED and its distribution to energy carriers and heating systems was estimated, as shown in the Supplementary File (spreadsheet "heating-energy-carrier"). Emission factors $EF_{GWP,k}$ were taken from Austria's Environment Agency [40], shown in the Appendix A Table A2.

2.2. Modelling the Material Flows of Construction Materials and Demolition Waste of the Updated Building Model of Vienna Considering Non- and Enhanced Circular Economy Scenarios

For modelling the material flows of construction materials and demolition waste in the updated building model of Vienna, material flow analysis (MFA) after Brunner and Rechberger [41] was used. Two types of MFA models were calculated. The first does

not consider an enhanced local circular economy in the building sector but assumes that demolition waste from Vienna are either exported to the neighbouring federal state of Lower Austria or recycled to other sectors than building construction. The second is an enhanced local circular economy scenario that assumes the maximum treatment of demolition waste in Vienna to produce secondary raw materials to be used in Vienna's building sector.

2.2.1. Material Flows of Construction Materials and Demolition Waste without Local Circular Economy in the Building Sector

The MFA model, which is shown in Figure 3, consists of seven processes, starting with 1. Production of construction materials and 2. Buildings. The inputs of construction materials into both processes are assumed to be the same, meaning that losses, for instance by clinker burning for cement, are not considered here. The material inputs of construction materials and outputs of demolition waste come from the updated material input and output model (see Section 2.1.3). The latter (material outputs of demolition waste) form the input into process 3. Demolition waste collection and transport, in which the demolition waste are distributed to the processes 4. Demolition waste management Lower Austria and process 5. Demolition waste management Vienna. The relevant data were taken from the waste management plan of Lower Austria [42]. In Lower Austria, the bulk of demolition waste are recycled, mainly in road construction in Lower Austria [30,42,43], while a smaller share is landfilled (process 6. Landfill Lower Austria). The incineration of demolition waste from Vienna in Lower Austria is of low relevance. The reason is that Vienna has the largest waste incineration capacity in Austria and imports rather than exports combustible waste. In Vienna, based on information from the only two operators of demolition waste treatment plants and landfills (ContraCon and LangesFeld [44,45]), a higher share of demolition waste is landfilled than in Lower Austria, while a smaller amount is recycled, also mainly in road construction. With respect to recycling, there is only a relevant backflow of demolition recycling materials generated in Vienna and used in Vienna (flow F5-1.1). This flow consists of brickwork contributing 10% of material demand in the cement industry [46], steel scrap which is entirely used to produce new steel, and waste wood of which 73% is recycled in new wood products [47].

2.2.2. Material Flows of Construction Materials and Demolition Waste with Local Circular Economy in the Building Sector

The MFA model for the local circular economy scenario is the same as in Figure 2. However, the difference is that there is a much stronger link between Vienna's demolition waste management and the construction industry of the city. This particularly counts for the mineral demolition waste of concrete, brickwork, and gravel and sand, which are, like the aforementioned steel and wood, also sought to be recycled in buildings in Vienna. Based on the strategies as defined in Lederer et al. [30], mineral demolition waste from buildings in Vienna are treated in Vienna or its vicinity, in order to produce recycling materials such as recycling aggregates from demolition waste concrete, debris, gravel and sand to be used in concrete, secondary raw materials from debris to produce cement, recycling aggregate from demolition waste debris for unbound use (e.g., as filler on flat roofs), or recycling wood and steel products (material flow F5-1.1 in the MFA-model in Figure 3). These strategies consider technical and legal limits for the use of recycling materials. In detail, these limits foresee that concretes (material flow F1-2.1 in Figure 2) can consist either of 29% recycling aggregate from demolished and processed concrete or gravel and sand, or 17% of recycling material from the coarse fraction of demolished and processed brickwork. According to the literature, all cements can consist of 20% of demolished and processed fine fractions of brickwork [48], instead of 10% as assumed based on data from Mauschitz on the current practise in the Austrian cement industry [46]. As before, waste steel can be recycled at 100% to steel (material flow F1-2.4) and waste wood (material flow F1-2.5 in Figure 3) can be recycled at 73% of the waste generated. The remaining wood is incinerated, due to its low quality [47]. For other waste such as glass, mineral wool, and polystyrene, no recycling is assumed, which has to do with lack of data, quality limitations, but also contents of potentially hazardous materials such as asbestos in mineral wool or CFCs in

Sustainability **2024**, 16, 7319 9 of 26

polystyrene. In Austria, however, these hazardous materials are usually removed manually before demolition [30]. Furthermore, reuse is not considered, since its contribution to a circular economy of construction materials considered in this study is negligible [30].




Figure 3. MFA model for buildings in Vienna. Concrete * from demolition can be present in concrete waste or debris waste, the latter being a mix of mineral demolition wastes. Brickwork ** consists of bricks, mortar, and plaster, and is like Gravel & Sand ** present in debris waste. Steel *** consists of construction steel and rebar.

2.3. Assessing the Scenarios without vs. with a Local Circular Economy of the Updated Building Model

In accordance with Vienna's and Austria's circular economy and waste management legislation and strategies, the following indicators were used for the sustainability assessment of both the scenarios defined in Section 2.2.

2.3.1. Heating Energy Demand (HED)

The first indicator is the HED in MWh/capita/yr and calculated as in Equation (3). The results for this indicator are not influenced by the circular economy scenarios. The HED is calculated for the years 1991–2020 ex-post and for 2021–2050 scenario-based, and the results are indicated for the years for which a HED reduction target in comparison to the base value (average annual value for the timespan 2005–2010) was aimed to be achieved in the Smart Climate City Strategy Vienna. This counts for the years 2030 (-20%) and 2040 (-30%). These reduction targets are similar to the modelled transition scenario for Austria by the *Umweltbundesamt* [29]. Not considered as a benchmark here in this study are any reduction targets of the Integrated National Energy- and Climate Plan, since this document was not ratified by the relevant parties in Austria, meaning that it is likely to be subject to changes before coming to force.

2.3.2. Direct Greenhouse Gas Emissions from Heating

The second indicator is the direct GHG emissions from heating, which are calculated as shown in Equation (4), Section 2.1.5. The results for this indicator are not influenced by the

circular economy scenarios, since only direct GHG emissions from heating are considered in the Smart Climate City Strategy Vienna. The GWP is calculated for the years 1991–2020 ex-post and 2021–2050 scenario-based, and the results are indicated for the years for which a GWP reduction target existed in comparison to the annual average of the years 2005–2010. This counts for the years 2030 (-30%) and 2040 (-100% GHG per capita).

2.3.3. Total Material Requirement

The second metric for the consumption-based material footprint is the total material requirement (TMR). For calculation of the $TMR_{net,t}$, data on construction material consumption, i.e., the material flows for the different materials $MF_{input,m,t}$, were modelled as shown in Section 2.1.3. Recycling materials substituting raw materials were subtracted, considering characterization factors for raw materials (CF_{TMR,m_raw}) and recycling materials (CF_{TMR,m_rec}) after Mostert and Bringezu [49]. Like in Watari et al. [50] and Oliveira Neto et al. [51], data for the $CF_{TMR,m}$ came from the Wuppertal Institute [52]. The same data were also used to calculate and monitor the TMR of Vienna in the Smart Climate City Strategy Vienna [25]. Table A2 provides an overview not only of the GWP emission factors, but also of the TMR characterization factors as used in this study. The calculation was performed using Equation (5):

$$TMR_{net,t} = \sum_{m=1}^{m=n} \left(MF_{input,m,t} \times CF_{TMR,m\ raw} - MF_{recycling,m,t} \times CF_{TMR,m\ rec} \right)$$
(5)

In detail, $MF_{input,m,t}$ is the material flow input into processing P2 Buildings that can be substituted by recycling materials, and $MF_{recycling,m,t}$ is the material flow of recycling materials. It is assumed that these recycling materials, summarized in material flow F5-1.1 in the MFA model in Figure 3, consist of first recycling aggregate from demolished concrete, brickwork, and gravel and sand, substituting natural aggregate to produce concrete or an unbound form (as filling material); second, the fine fraction of processed brickwork to be used for the production of cement for concrete; third, demolished steel that can be used to produce steel; and fourth, demolished wood that can be used to produce wood fibre boards. For details on these recycling routes, see Lederer et al. [30].

The $TMR_{net,t}$ was calculated for the year 2019, which is the base year, and for the years 2021–2050 on a scenario basis. The results are indicated for the years with a reduction target, namely 2030 (-30%), 2040 (-40%), and 2050 (-50% of the $TMR_{net,t}$ per capita if compared to the year 2019). The unit is Mg/capita/year.

2.3.4. Circular Material Use Rate

An important indicator in Austria's Circular Economy Strategy [53] is the circular material use rate (CMUR), which is the content of recycled materials in products. The CMUR is usually calculated for economic entities, like national states. For these, only recycling materials originating from the entities are considered, but not recycling materials which are imported [54]. For a particular sector, like buildings, and a not national but regional entity, like a federal state, there are no general guidelines for calculating the CMUR. For this reason, the CMUR for buildings in Vienna is calculated as defined in this study by Equation (6).

$$CMUR_{t} = \sum_{m=1}^{m=n} MF_{recycling,m,t} / MF_{input,m,t}$$
 (6)

where $MF_{input,m,t}$ is the material input calculated after Equation (1) (Section 2.1.3) and $MF_{recycling,m,t}$ is the recycling material provided to cover parts of this material input for material m in year t. In the MFA model in Figure 3, $MF_{recycling,m,t}$ equals material flow F5-1.1 Recycling materials, while $\sum_{m=1}^{m=n} MF_{input,m,t}$ is the sum of the material flows F1-2.1 to F1-2.8, which are construction materials such as concrete, brickwork, etc. Recycling materials that may come from outside Vienna or recycling materials that origin from sectors other than buildings are not counted.

3. Results and Discussion

The results section first shows the model result based on the updates (Section 3.1), then the material flows considering demolition waste management (Section 3.2), and finally the sustainability assessment of Vienna's building sector (Section 3.3).

3.1. Updated Material Inputs and Outputs, Heating Energy Demand, and Greenhouse Gases of Vienna's Building Sector

The updated material input and output model is shown in Figure 4 and in the Supplementary File spreadsheet (Table "S11 Results per-captia"). Even though it was assumed that the scenario 2021–2050 follows the DEMO-scenario from Lederer et al. [17], the material input after 2021 is smaller than in the preceding years. The reason for this is that it was assumed that the NFA per person remains constant, while it was expanded in recent decades. This influences the material inputs. In other studies, particularly Heeren and Hellweg for Switzerland and Soonsawad et al. for Canberras, decreasing material inputs in the building stock were also predicted [55,56]. The reasons for this are manifold, including population decrease in the case of Switzerland, but also a saturation of the building stock in both cases. On the output side, the amount of waste from the demolition of buildings starts with a high value, which is reduced until 2050 to a level that was experienced in the year 2001. This is in contrast to the assumptions from Heeren and Hellweg, who assumed higher material outputs in the future, caused by the refurbishment of buildings [55].




Figure 4. Updated material input and output model for buildings in Vienna 1991–2050.

Figure 5 shows the updated HED model of Vienna for 1991–2050. The data are also displayed in the Supplementary File spreadsheet (Table "S11 Results per-capita" and "S9 Results_heating-energy"). The result first shows the good agreement between the modelled and the measured data from Gollner [57] for the years for which data were available (1991–2020). Furthermore, the model shows the decline in the per capita HED since the year 2001. This is clearly an achievement not only of new low-energy buildings substituting old high-energy consuming buildings, but also of thermal renovation of existing buildings [13,31]. With respect to future HED, the results are in line with studies from the UK and Finland, even though in these studies, the temperature increase due to global warming has a much higher impact than in this study, where this factor was not considered [58,59]. Furthermore, the reduction in HED in Vienna as modelled in this study is stronger than in the cities investigated by Harris et al. [60]. However, the study of Harris et al. modelled the total energy demand of cities, and not only the HED. What is remarkable

in this study for Vienna is the comparatively high HED of service buildings, which are only $13~\text{m}^2$ NFA/capita in Vienna if compared to $41~\text{m}^2$ NFA/capita for residential buildings. This means that the potential to save energy for the HED in Vienna is larger for service buildings, despite their smaller relevance in terms of the HED.




Figure 5. Updated HED model for buildings in Vienna 1991–2050.

The updated greenhouse gas emission model considering the direct greenhouse gasses from heating is shown in Figure 6. Like for the HED, the GHG for heating has declined since the year 2001. This decline is even stronger, since not only less energy is used, but the energy sources also produce less GHG emissions than, for instance, oil or natural gas. However, and this will be shown later, this decline is not sufficient to meet the GHG emission reduction targets of Vienna, nor also Austria and the EU 27. In comparison to other cities, however, Harris et al. [60] shows that only Copenhagen achieves higher GHG reductions than the HED-caused GHG emissions in the building sector of Vienna, even in a business-as-usual scenario [60]. Therefore, Vienna should look at cities like Copenhagen as role models for their own transformation.

3.2. Material Flows of Construction Materials and Demolition Wastes of the Updated Building Model of Vienna with and witout Enhanced Circular Economy Scenarios

The MFA for buildings in Vienna for the year 2030 without an enhanced local circular economy is shown in Figure 7, and the MFA for the enhanced local circular economy scenario for the year 2030 is shown in Figure 8. Figures A1–A5 in the Appendix A show the MFAs for the year 2019 (status quo), and for the years 2040, and 2050 (with and without an enhanced local circular economy). A comparison of the figures for the scenario without local circular economy in the year 2030 (Figure 7) with the local circular economy scenario for the year 2030 (Figure 8) shows that in the first, the bulk of wastes are still exported and not recycled in Vienna in the building sector. In detail, in the year 2030, without a local circular economy, in total 3,146,040 Mg/yr have to be imported (see Figure 7), while with an enhanced local circular economy, the import reduces to 2,295,559 Mg/yr (see Figure 8). In the latter case, 902,315 Mg/yr of secondary raw materials from building demolition in Vienna will be used as construction materials for buildings newly constructed in Vienna. Since it was assumed that demolition activities will decrease until 2050, as foreseen in the Smart Climate City Strategy Vienna [25], the amount of raw materials consumed in process 2. Buildings will also decrease to 2,931,154 Mg/yr in the year 2050 (see Figures A4 and A5 in the Appendix A). Since less demolition waste is available in 2050, the amount of secondary raw materials provided also decreases to 629,854 Mg/yr in the enhanced local recycling

scenario (Figure A5). As a result, slightly more raw materials have to be imported in the year 2050 (2,301,300 Mg/yr) than in the year 2030 (2,295,559 Mg/yr), which is detrimental to achieving a maximum CMUR. Furthermore, the results are in contrast to findings from Zhang et al. for the Netherlands, where most imports of raw materials for building construction (except limestone and cement) are projected to decrease [61]. The reason for this difference is that in Zhang et al., the demolition rate of buildings does not decrease, while in this study, it did, since it was assumed that a lower number of buildings were demolished. However, this also reflects the differences in the political agenda of how to achieve a decarbonized and circular building stock.




Figure 6. Updated direct GHG emission model from heating for buildings in Vienna 1991–2050.




Figure 7. MFA for buildings in Vienna 2030 without enhanced local circular economy.




Figure 8. MFA for buildings in Vienna 2030 with enhanced local circular economy.

3.3. Assessing the Updated Building Model

3.3.1. Heating Energy Demand and Greenhouse Gas Emissions

Table 3 shows the results of the HED and GHG emissions of the defined development pathway. As already mentioned, there is no difference in these indicators for the two circular economy scenarios. The results show that the defined DEMO-BAU development pathway can reach the reduction targets of the *Smart Climate City Strategy Vienna* for the HED. As shown in Haas et al. [31] and Hoxha et al. [62], a higher number of buildings being renovated by thermal insulation annually can further reduce the HED. However, sufficient incentives therefore have to be provided [31,62].

Table 3. Modelled HED and GWP for the heating of buildings in Vienna in 2030, 2040, and 2050, compared to reduction targets (base year annual average 2005–2010).

Indicator Value		Unit	2005	2030	2040	2050
LIED	Modelled value Value that has to be achieved	kwh/cap/yr	6620	4972 5296	4372 4634	3892
HED -	Modelled value Value that has to be achieved	% of the average 2005–2010	100% 100%	75% 80%	66% 70%	59%
GHG -	Modelled value Value that has to be achieved	kg CO _{2-eq.} /cap/yr	1217	805 548	692 0	602 0
GAG -	Modelled value Value that has to be achieved	% of the average 100%		66% 45%	57% 0%	49% 0%

With respect to GHG emissions, the figures look worse for both the 2030 and the 2040 target. It must be said that all major stakeholders at different levels, from Vienna over Austria to the EU 27, agreed to achieve carbon neutrality by earliest in 2040, latest in 2050 [22,63]. To reduce the GHG emissions for the HED of buildings in Vienna, next to reducing the HED, a change in the heating systems is required. For Vienna, this is

a challenge, considering the high share of decentralized natural gas-fed boiler heating systems that exist [31]. However, with a lower HED, this is also easier to achieve.

3.3.2. Total Material Requirement and Circular Material Use Rate with a Local Circular Economy Scenario

Table 4 shows the results of the TMR and CMUR calculation of the defined development pathway in Vienna. With respect to the TMR, the reduction targets as defined in the Smart Climate City Strategy Vienna were easily met by the modelled values for the years 2030, 2040, and 2050. The reason for this is on the one hand a decrease in material consumption due to a lower demolition of buildings, and on the other hand the enhanced local recycling of demolition wastes. The latter has also been shown by Zhang et al. for concrete recycling in the Netherlands [64]. Contrary to the positive development of the TMR, the CMUR declines from 28% in the year 2030 to 21% in the year 2050 due to the lower amounts of recycling material available, which is caused by lower number of buildings being demolished. When solely looking at the CMUR, this development is negative, since the CMUR aims to achieve a maximum possible value in sustainable development [54]. However, since a circular economy aims to reduce primary raw material consumption, the benefits of reducing the TMR outweigh the costs of a decreasing CMUR, since recycling, which is actually measured by the CMUR, is just a tool for the circular economy and not an objective of the circular economy. This contradiction is interesting, not only for research, but also for policy-selecting circular economy indicators.

Table 4. TMR and CMUR f	or buildings in Vienna in 20	30, 2040, and 2050, com	pared to 2019.

Indicator	Value	Unit	2019	2030	2040	2050		
	Modelled value for primary raw materials		3929	2568	2318	2132		
	Modelled value for reduction by local recycling	kg/cap/yr	-37	-681	-550	-426		
TMR	Modelled value total	-	3892	1887	1769	1705		
-	Value that has to be achieved	-	3892	2725	2335	1946		
-	Modelled value total	% of the year	100%	48%	45%	44%		
-	Value that has to be achieved	2019	100%	70%				
CMUR	Modelled value Value that has to be achieved	% of material input	1% 12% ⁽¹⁾	28% 18% ⁽²⁾	25% 18% ⁽²⁾	21% 18% ⁽³⁾		

^{(1) 12%} refers to the national level in Austria, as there are no data available for Vienna [53]. (2) The 18% refers to the national target in Austria [53]. (3) For the years 2040 and 2050, no national target was defined, so the target from the year 2030 was used.

4. Conclusions

Cities are not only important consumers of energy and resources but also producers of emissions and waste. For the material resources and waste part, a circular economy can play an important role to mitigate negative impacts on the environment, even under a scenario where an excessive demolition of buildings, an in general unsustainable practise, prevails. This was shown for the case study of Vienna, as analyzed in this study. However, for a reduction in energy consumption and the mitigation of greenhouse gas emissions, more ambitions are still required, particularly increasing the renovation of buildings by thermal insulation and transforming energy production for the heating of buildings. Together with a circular economy for demolition wastes and construction materials, this will be the key to sustainable urban development.

Supplementary Materials: The following supporting information can be downloaded at: https://www.mdpi.com/article/10.3390/su16177319/s1, Supplementary File spreadsheet.

Author Contributions: Conceptualization, J.L.; methodology, J.L.; software, J.L.; validation, J.L.; formal analysis, J.L.; investigation, J.L.; resources, J.L.; data curation, J.L. and D.B.; writing—original draft preparation, J.L.; writing—review and editing, D.B.; visualization, J.L.; supervision, J.L.; project administration, J.L.; funding acquisition, J.L. and D.B. All authors have read and agreed to the published version of the manuscript.

Funding: This research was funded by Vienna Science and Technology Funds (WWTF), Funding Program Environmental Systems Research 2017—Urban Environments, Funding No. ESR17-067, Project TransLoC: Transformation of Cities into a Low Carbon Future and its Impact on Urban Metabolism, Environment, and Society; Austrian Research Promotion Agency FFG, Funding Program Leitprojekt-Kreislaufführung von Baustoffen und Gebäudeteilen mit KI-Unterstützung, Project KrAIsbau.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: All data used for this study are available in the article or other articles cited, particularly references [17,18,30,35]. In addition, a Supplementary Data File with all data is available.

Conflicts of Interest: The authors declare no conflicts of interest.

Appendix A

Table A1. Material intensity coefficients (MCIs) for the material input (MCI_{input}) and output (MCI_{output)} of different building types according to their use, age, and renovation category. Renovated refers to thermal renovation.

N/ (1 1	Building Age and	MICinput	MICoutput	MICinput	MICoutput	MICinput	MICoutput	MICinput	MICoutput
Material	Renovation Category	Residential Buildings Service Buildings		Buildings	Industria	l Buildings	Other B	Buildings	
Concrete	1800–1918	-	250.6	-	183.0	-	917.5	-	81.4
	1800-1918 Renovated	-	-	-	-	-	-	-	-
	1800–1918 Attic extension	920.3	-	-	-	-	-	-	-
	1919–1945	-	519.2	-	836.6	-	1322.3	-	1333.3
	1919–1945 Renovated	-	-	-	-	-	-	-	-
	1919–1945 Attic extension	920.3	-	-	-	-	-	-	-
	1946–1980	-	1370.7	-	1688.8	-	1499.5	-	1561.0
	1946-1980 Renovated	-	-	-	-	-	-	-	-
	1981–2000	1700.1	1700.1	1822.5	1822.5	1189.7	1189.7	1755.8	1755.8
	2001–2050	1664.9	1664.9	1533.1	1533.1	1905.0	1905.0	1852.7	1852.7
Brick	1800–1918	-	1888.8	-	1747.5	-	1212.7	-	2031.5
	1800-1918 Renovated	-	-	-	-	-	-	-	-
	1800–1918 Attic extension	224.2	175.4	-	-	-	-	-	-
	1919–1945	-	1518.4	-	1298.9	-	1144.7	-	703.8
	1919–1945 Renovated	-	-	-	-	-	-	-	-
	1919–1945 Attic extension	224.2	175.4	-	-	-	-	-	-
	1946–1980	-	818.9	-	136.1	-	370.3	-	211.9
	1946–1980 Renovated	-	-	-	-	-	-	-	-
	1981–2000	510.2	510.2	38.6	38.6	10.8	10.8	523.3	523.3
	2001–2050	273.9	273.9	61.0	61.0	192.0	192.0	208.9	208.9
Gravel	1800–1918	-	164.0	-	149.9	-	174.1	-	110.2
	1800–1918 Renovated	-	-	-	-	-	-	-	-
	1800–1918 Attic extension	3.6	76.8	-	-	-	-	-	-
	1919–1945	-	172.0	-	134.8	-	165.3	-	77.7

Table A1. Cont.

Material	Building Age and Renovation Category	MICinput	MICoutput	MICinput	MICoutput	MICinput	MICoutput	MICinput	MICoutput
Material		Residentia	l Buildings	Service l	Buildings	Industria	l Buildings	Other B	Buildings
	1919–1945 Renovated	-	-	-	-	-	-	-	-
	1919–1945 Attic extension	3.6	76.8	-	-	-	-	-	-
	1946–1980	-	152.5	-	143.9	-	105.4	-	151.2
	1946-1980 Renovated	-	-	-	-	-	-	-	-
	1981–2000	157.2	157.2	121.0	121.0	106.4	106.4	151.3	151.3
	2001–2050	149.5	149.5	118.0	118.0	136.8	136.8	152.3	152.3
Wood	1800–1918	-	44.6	-	43.9	-	31.2	-	62.3
	1800–1918 Renovated	-	-	-	-	-	-	-	-
	1800–1918 Attic extension	23.0	30.5	-	-	-	-	-	-
	1919–1945	-	40.1	-	28.9	-	43.7	-	19.1
	1919-1945 Renovated	-	-	-	-	-	-	-	-
	1919–1945 Attic extension	23.0	30.5	-	-	-	-	-	-
	1946–1980	-	15.1	-	8.8	-	5.5	-	30.6
	1946–1980 Renovated	-	-	-	-	-	-	-	-
	1981–2000	13.7	13.7	-	-	-	-	4.4	4.4
	2001–2050	11.8	11.8	9.3	9.3	-	-	12.2	12.2
Steel	1800–1918	-	9.1	-	7.2	-	42.6	-	1.9
	1800–1918 Renovated	-	-	-	-	-	-	-	-
	1800–1918 Attic extension	58.9	-	-	-	-	-	-	-
	1919–1945	-	8.7	-	14.1	-	138.7	-	41.8
	1919–1945 Renovated	-	-	-	-	-	-	-	-
	1919–1945 Attic extension	58.9	-	-	-	-	-	-	
	1946–1980	-	34.9	-	49.1	-	42.3	-	38.5
	1946–1980 Renovated	-	-	-	-	-	-	-	-
	1981–2000	99.7	99.7	116.4	116.4	127.7	127.7	269.8	269.8
	2001–2050	226.2	226.2	91.4	91.4	125.2	125.2	104.1	104.1
Glass	1800–1918	_	4.7	-	5.0	-	2.0	_	0.9
	1800–1918 Renovated	8.5	-	3.1	_	4.3	_	3.0	
	1800–1918 Attic extension	2.9	1.0	-		-	_	-	_
	1919–1945	-	5.2	-	2.9	-	3.8	-	3.4
	1919–1945 Renovated	7.2	-	3.0	-	8.0	_	3.4	_
	1919–1945 Attic extension	2.9	1.0	-	_	-	_	-	
	1946–1980	-	4.1	-	3.4	-	9.3	-	9.1
	1946–1980 Renovated	6.3	-	3.1		4.1	_	2.9	_
	1981–2000	4.4	4.4	3.3	3.3	3.5	3.5	3.3	3.3
	2001–2050	6.0	6.0	3.3	3.3	6.9	6.9	5.1	5.1
MinWool	1800–1918		0.7	_	1.3	-	1.5	-	0.4
	1800–1918 Renovated	3.1	-	1.9	-	0.5	-	1.2	-
	1800–1918 Attic extension	6.7	0.0	-	_	-	-	-	_
	1919–1945	-	2.5	-	1.2	-	0.5	-	3.6
	1919–1945 Renovated	2.7	<u>-</u>	1.9	-	0.9	-	1.4	
	1919–1945 Attic extension	6.7	0.0	-	<u>-</u>	-	-	-	
	1946–1980	-	1.3	-	0.4	_	-	-	3.0

Table A1. Cont.

	Building Age and Renovation Category	MICinput	MICoutput	MICinput	MICoutput	MICinput	MICoutput	MICinput	MICoutput
Material		Residentia	l Buildings	Service 1	Buildings	Industrial	Buildings	Other B	uildings
	1981–2000	1.4	1.4	0.4	0.4	-	-	0.9	0.9
	2001–2050	2.2	2.2	2.1	2.1	0.8	0.8	2.1	2.1
Polystyrene	1800–1918	-	0.6	-	0.5	-	0.6	-	-
	1800–1918 Renovated	6.5	-	3.5	-	3.9	-	3.9	-
	1800–1918 Attic extension	2.4	-	-	-	-	-	-	-
	1919–1945	-	0.6	-	0.7	-	0.9	-	0.8
	1919–1945 Renovated	5.5	-	3.5	-	7.3	-	4.4	-
	1919–1945 Attic extension	2.4	-	-	-	-	-	-	-
	1946–1980	-	0.5	-	1.1	-	3.9	-	1.3
	1946–1980 Renovated	4.8	-	3.6	-	3.7	-	3.8	-
	1981–2000	5.2	5.2	3.5	3.5	1.0	1.0	4.1	4.1
	2001–2050	4.6	4.6	3.9	3.9	6.3	6.3	6.6	6.6

Table A2. Emission factors (EFs) and characterization factors (CFs) to calculate the GWP and TMR for the use of different building materials and heating energy sources.

Material m	CF _{TMR,m_raw} in [kg/kg]	Material m	CF _{TMR,m_rec} in [kg/kg]	Energy k	EF _{GWP,k} of HED in [kg/kwh]
Concrete	1.3300	Recycling material from concrete to substitute natural aggregate in concrete	1.420	District heating	0.2000
Brickwork	1.9700	Recycling material from brickwork to substitute natural aggregate in concrete	1.420	Wood	0.0120
Gravel and sand	1.0100	Recycling material from gravel and sand to substitute natural aggregate in concrete	1.420	Renewables	0.0638
Wood	5.4000	Recycling material from brickwork to substitute raw materials for cement	1.420	Electricity	0.2190
Iron and steel	4.8000	Recycling material from brickwork to substitute gravel and sand	1.420	Hard coal	0.3320
Glass	2.9500	Recycling material from gravel and sand to substitute gravel & sand	1.420	Heating oil	0.3320
Mineral wool	4.3300	Recycling material from wood to substitute wood	3.440	Natural gas	0.2680
Polystyrene	2.5000	Recycling material from steel to substitute iron ore	6.670		




Figure A1. MFA for buildings in Vienna 2019 without an enhanced local circular economy.




Figure A2. MFA for buildings in Vienna 2040 without an enhanced local circular economy.




Figure A3. MFA for buildings in Vienna 2040 with an enhanced local circular economy.




Figure A4. MFA for buildings in Vienna 2050 without an enhanced local circular economy.




Figure A5. MFA for buildings in Vienna 2050 with an enhanced local circular economy.

References

- 1. Ritchie, H.; Roser, M. Urbanization. 2018. Available online: https://ourworldindata.org/ (accessed on 27 July 2024).
- 2. Kalmykova, Y.; Rosado, L.; Patrício, J. Resource consumption drivers and pathways to reduction: Economy, policy and lifestyle impact on material flows at the national and urban scale. *J. Clean. Prod.* **2016**, *132*, 70–80. [CrossRef]
- 3. Schiller, G.; Roscher, J. Impact of urbanization on construction material consumption: A global analysis. *J. Ind. Ecol.* **2023**, 27, 1021–1036. [CrossRef]
- 4. Petit-Boix, A.; Leipold, S. Circular economy in cities: Reviewing how environmental research aligns with local practices. *J. Clean. Prod.* **2018**, 195, 1270–1281. [CrossRef]
- 5. Prendeville, S.; Cherim, E.; Bocken, N. Circular Cities: Mapping Six Cities in Transition. *Environ. Innov. Soc. Transit.* **2018**, 26, 171–194. [CrossRef]
- Marin, J.; Alaerts, L.; Van Acker, K. A Materials Bank for Circular Leuven: How to Monitor 'Messy' Circular City Transition Projects. Sustainability 2020, 12, 10351. [CrossRef]
- 7. Savini, F. The economy that runs on waste: Accumulation in the circular city. J. Environ. Policy Plan. 2019, 21, 675–691. [CrossRef]
- 8. Barles, S. Urban Metabolism of Paris and Its Region. J. Ind. Ecol. 2009, 13, 898–913. [CrossRef]
- 9. Chen, S.; Chen, B. Network Environ Perspective for Urban Metabolism and Carbon Emissions: A Case Study of Vienna, Austria. *Environ. Sci. Technol.* **2012**, *46*, 4498–4506. [CrossRef]
- 10. Christis, M.; Athanassiadis, A.; Vercalsteren, A. Implementation at a city level of circular economy strategies and climate change mitigation—The case of Brussels. *J. Clean. Prod.* **2019**, 218, 511–520. [CrossRef]
- 11. Gassner, A.; Lederer, J.; Kanitschar, G.; Ossberger, M.; Fellner, J. Extended ecological footprint for different modes of urban public transport: The case of Vienna, Austria. *Land Use Policy* **2018**, 72, 85–99. [CrossRef]

12. Rosado, L.; Kalmykova, Y.; Patrício, J. Urban metabolism profiles. An empirical analysis of the material flow characteristics of three metropolitan areas in Sweden. *J. Clean. Prod.* **2016**, 126, 206–217. [CrossRef]

- 13. van Oorschot, J.; Sprecher, B.; Rijken, B.; Witteveen, P.; Blok, M.; Schouten, N.; van der Voet, E. Toward a low-carbon and circular building sector: Building strategies and urbanization pathways for the Netherlands. *J. Ind. Ecol.* **2023**, 27, 535–547. [CrossRef]
- 14. Lederer, J.; Ott, C.; Brunner, P.H.; Ossberger, M. The life cycle energy demand and greenhouse gas emissions of high-capacity urban transport systems: A case study from Vienna's subway line U2. *Int. J. Sustain. Transp.* **2016**, *10*, 120–130. [CrossRef]
- 15. Wurzer, G.; Lorenz, W.; Forster, J.; Bindreiter, S.; Lederer, J.; Gassner, A.; Mitteregger, M.; Kotroczo, E.; Pöllauer, P.; Fellner, J. M-DAB: Towards re-using material resources of the city. In Proceedings of the 38th eCAADe, Anthropologic—Architecture and Fabrication in the Cognitive Age, Berlin, Germany, 17–19 September 2020; pp. 127–132. Available online: http://hdl.handle.net/20.500.12708/65012 (accessed on 28 July 2024).
- 16. Gassner, A.; Lederer, J.; Kovacic, G.; Mollay, U.; Schremmer, C.; Fellner, J. Projection of material flows and stocks in the urban transport sector until 2050–A scenario-based analysis for the city of Vienna. *J. Clean. Prod.* **2021**, 311, 127591. [CrossRef]
- 17. Lederer, J.; Gassner, A.; Fellner, J.; Mollay, U.; Schremmer, C. Raw materials consumption and demolition waste generation of the urban building sector 2016–2050: A scenario-based material flow analysis of Vienna. *J. Clean. Prod.* **2021**, 288, 125566. [CrossRef]
- 18. Lederer, J.; Gassner, A.; Keringer, F.; Mollay, U.; Schremmer, C.; Fellner, J. Material flows and stocks in the urban building sector: A case study from Vienna for the years 1990–2015. *Sustainability* **2019**, *12*, 300. [CrossRef]
- 19. Gassner, A.; Lederer, J.; Fellner, J. Material stock development of the transport sector in the city of Vienna. *J. Ind. Ecol.* **2020**, 24, 1364–1378. [CrossRef]
- 20. Kleemann, F.; Lederer, J.; Rechberger, H.; Fellner, J. GIS-based Analysis of Vienna's Material Stock in Buildings. *J. Ind. Ecol.* **2017**, 21, 368–380. [CrossRef]
- 21. Cavaleiro de Ferreira, A.; Fuso-Nerini, F. A Framework for Implementing and Tracking Circular Economy in Cities: The Case of Porto. *Sustainability* **2019**, *11*, 1813. [CrossRef]
- 22. Deistler, J.; Homeier, I.; Lengauer, C.; Pangerl, E.; Rücker, L.; Lutter, J.; Cerveny, M.; Bartik, H.; Hofinger, J.; Veigl, A. *Smart Klima City Strategie Wien (Smart Climate City Strategy Vienna)*; Magistrat der Stadt Wien: Vienna, Austria, 2022; Available online: https://smartcity.wien.gv.at/ (accessed on 27 July 2024).
- 23. Adams, K.T.; Osmani, M.; Thorpe, T.; Thornback, J. Circular economy in construction: Current awareness, challenges and enablers. *Proc. Inst. Civ. Eng. Waste Resour. Manag.* **2017**, *170*, 15–24. [CrossRef]
- 24. Liedtke, C.; Bienge, K.; Wiesen, K.; Teubler, J.; Greiff, K.; Lettenmeier, M.; Rohn, H. Resource Use in the Production and Consumption System—The MIPS Approach. *Resources* **2014**, *3*, 544–574. [CrossRef]
- 25. Eisenmenger, N.; Kaufmann, L.; Kalt, G.; Dorninger, C.; Perkovic, M.; Lederer, J.; Fellner, J.; Lutter, S. CO₂-und Material-Fußabdruck für Wien (CO₂- and Material footprint of Vienna); University of Natural Resources and Life Sciences, Technische Universitaet Wien, Vienna University of Economics and Buisnesses: Vienna, Austria, 2022.
- Veigl, A.; Watzak-Helmer, M.; Cerveny, M. Wiens Klima- & Energieziele für 2030 & 2050; Urban Innovation Vienna: Vienna, Austria, 2019.
- 27. ENTSO-E. Stromversorgung der Vergangenen 52 Wochen, Stromversorgung in den Vergangenen 30 Tagen Bzw. 12 Monaten. ENTSO-E, Ed. 2024. Available online: https://energie.gv.at/strom/strom (accessed on 27 July 2024).
- 28. BMK. Integrierter nationaler Energie- und Klimaplan für Österreich Periode 2021–2030 (Integrated National Energy and Climate Plan for Austria Period 2021–2030). Draft for Public Consultation; Bundesministerium für Klimaschutz, Umwelt, Energie, Mobilität; Innovation und Technologie (BMK): Vienna, Austria, 2023.
- 29. Krutzler, T.; Wasserbaur, R.; Schindler, I. Energie- und Treibhausgasszenarien 2023 (Energy and Greenhouse Gas Scenarios 2023); Umweltbundesamt: Vienna, Austria, 2023.
- 30. Lederer, J.; Gassner, A.; Kleemann, F.; Fellner, J. Potentials for a circular economy of mineral construction materials and demolition waste in urban areas: A case study from Vienna. *Resour. Conserv. Recycl.* **2020**, *161*, 104942. [CrossRef]
- 31. Haas, R.; Siebenhofer, M.; Lederer, J.; Ajanovic, A. Historical Evolution and Scenarios Up to 2050 of Heating Energy Consumption and CO₂ Emissions of Residential Buildings in Vienna. *J. Energy Power Technol.* **2022**, *4*, 30. [CrossRef]
- 32. Stadt_Wien. Nicht gefährlicher Abfall—Abfallmengen in Wien (Non-Hazardous Waste—Waste Quantities in Vienna). Available online: https://www.wien.gv.at/umweltschutz/abfall/nicht-gefaehrliche-abfallmenge.html (accessed on 27 July 2024).
- 33. Statistics_Austria. 2005 bis 2020 Fertiggestellte Wohnungen Nach Gebäudeeigenschaften, Art der Bautätigkeit und Bundesländern (2005 to 2020 Completed Living Units according to Type of Building, Type of Construction Activity and Federal States), 16.11.2021 ed.; Statistics Austria: Vienna, Austria, 2021.
- 34. Wohnfonds_Wien. Anzahl der Thermisch Sanierten Wohneinheiten in Wien Nach Bauperiode (Number of Thermal Renovated Living Units after Construction Period); Lederer, J., Ed.; Wien: Vienna, Austria, 2022.
- 35. Lederer, J.; Fellner, J.; Gassner, A.; Gruhler, K.; Schiller, G. Determining the material intensities of buildings selected by random sampling: A case study from Vienna. *J. Ind. Ecol.* **2021**, 25, 848–863. [CrossRef]
- 36. Müller, A. Energy Demand Assessment for Space Conditioning and Domestic Hot Water: A Case Study for the Austrian Building Stock; Technische Universität Wien: Vienna, Austria, 2015.

Sustainability **2024**, 16, 7319 25 of 26

37. OIB. Richtlinien des Österreichischen Instituts für Bautechnik (Standards of the Austrian Institut for Construction Technology). In OIB-Richtlinie 6 Energieeinsparung und Wärmeschutz (OIB Standard 6 Energy Supply and Thermal Insulation); Österreichischen Instituts für Bautechnik (OIB): Vienna, Austria, 2015; Volume OIB-330.6-009/15.

- 38. Stadt_Wien. *Heating Demand of Restorated Apartments before and after Restoration*, 08.10.2021 ed.; Magistrat Wien—Magistratsabteilung 20—Energieplanung: Vienna, Austria, 2021.
- 39. Bayer, G.; Sturm, T.; Steininger, M. *Energieflüsse in Bürogebäuden*; Österreichische Gesellschaft für Umwelt und Technik (ÖGUT): Wien, Austria, 2014.
- 40. Umweltbundesamt. Berechnung von Treibhausgas (THG)-Emissionen Verschiedener Energieträger. Available online: https://secure.umweltbundesamt.at/co2mon/co2mon.html (accessed on 27 July 2024).
- 41. Brunner, P.H.; Rechberger, H. Handbook of Material Flow Analysis: For Environmental, Resource, and Waste Engineers, 2nd ed.; CRC Press: Boca Raton, FL, USA, 2016.
- 42. Land_Niederösterreich. NIederösterreichischer Abfallwirtschaftsplan (Waste Management Plan of Lower-Austria); Land Niederösterreich, Gruppe Raumordnung, Umwelt und Verkehr (Federal State of Lowwer-Austria, Group Spatial Planning, Environment and Transport): St. Pölten, Austria, 2018.
- 43. Bernhardt, A.; Kleemann, F.; Neubauer, C.; Neubauer, M.; Walter, B. Datenanalyse zur Behandlung von Mineralischen Bau- und Abbruchabfällen in Österreich—Detailstudie zum Bundes-Abfallwirtschaftsplan (Data Analysis on the Treatment of Mineral Construction and Demolition Wastes in Austria—Detailed Study for the Federal Waste Management Plan); Umweltbundesamt (Federal Environment Agency): Vienna, Austria, 2019.
- 44. ContraCon. *Amounts and Types of Demolition Waste Treated and Recycling Materials Produced*; Lederer, J., Ed.; ContraCon: Vienna, Austria, 2023. Available online: https://www.contracon.at/ (accessed on 27 July 2024).
- 45. LangesFeld. *Amounts and Types of Demolition Waste Treated and Recycling Materials Produced*; Lederer, J., Ed.; LangesFeld: Vienna, Austria, 2023. Available online: https://langesfeld.at/ (accessed on 27 July 2024).
- 46. Mauschitz, G. Emissionen aus Anlagen der Österreichischen Zementindustrie—Berichtsjahr 2016 (Emissions from Plants of the Austrian Cement Industry—Reporting Year 2016); TU Wien: Vienna, Austria, 2017.
- 47. BMK. Bundes-Abfallwirtschaftsplan (BAWP) 2023 Teil 1 (Federal Waste Management Plan 2023 Part 1); Bundesministerin für Klimaschutz, Umwelt, Energie, Mobilität, Innovation und Technologie (BMK): Vienna, Austria, 2023.
- 48. Zeitlhofer, H.; Peyerl, M.; Krispel, S. Evaluierung des Einsatzes Alternativer Rohstoffe in der Klinkerproduktion zur Minderung der Treibhausgasemissionen (Evaluation of the Use of Alternative Raw Materials in the Clinker Production for the Reduction of Greenhouse Gas Emissions); Smart Minerals: Vienna, Austria, 2018; p. 61.
- 49. Mostert, C.; Bringezu, S. Measuring Product Material Footprint as New Life Cycle Impact Assessment Method: Indicators and Abiotic Characterization Factors. *Resources* **2019**, *8*, 61. [CrossRef]
- 50. Watari, T.; McLellan, B.C.; Giurco, D.; Dominish, E.; Yamasue, E.; Nansai, K. Total material requirement for the global energy transition to 2050: A focus on transport and electricity. *Resour. Conserv. Recycl.* **2019**, *148*, 91–103. [CrossRef]
- 51. Oliveira Neto, G.C.; Correia, J.M. Environmental and economic advantages of adopting reverse logistics for recycling construction and demolition waste: A case study of Brazilian construction and recycling companies. *Waste Manag. Res.* **2019**, *37*, 176–185. [CrossRef] [PubMed]
- 52. Wuppertal_Institute. *Material Intensity of Materials, Fuels, Transport Services, Food*; Wuppertal Institute for Climate, Environment and Energy GmbH: Wuppertal, Germany, 2014.
- 53. BMK. *Die österreichische Kreislaufwirtschaft. Österreich auf dem Weg zu Einer Nachhaltigen und Zirkulären Gesellschaft*; Bundesministerium für Klimaschutz, Umwelt, Energie, Mobilität, Innovation und Technologie (BMK): Vienna, Austria, 2021.
- 54. Moraga, G.; Huysveld, S.; Mathieux, F.; Blengini, G.A.; Alaerts, L.; Van Acker, K.; de Meester, S.; Dewulf, J. Circular economy indicators: What do they measure? *Resour. Conserv. Recycl.* **2019**, *146*, 452–461. [CrossRef]
- 55. Heeren, N.; Hellweg, S. Tracking Construction Material over Space and Time: Prospective and Geo-referenced Modeling of Building Stocks and Construction Material Flows. *J. Ind. Ecol.* **2019**, *23*, 253–267. [CrossRef]
- 56. Soonsawad, N.; Marcos-Martinez, R.; Schandl, H. City-scale assessment of the material and environmental footprint of buildings using an advanced building information model: A case study from Canberra, Australia. *J. Ind. Ecol.* **2024**, *28*, 247–261. [CrossRef]
- 57. Gollner, M. Nutzenergieanalyse. Available online: https://www.statistik.at/statistiken/energie-und-umwelt/energie/nutzenergieanalyse (accessed on 22 April 2022).
- 58. Jylhä, K.; Jokisalo, J.; Ruosteenoja, K.; Pilli-Sihvola, K.; Kalamees, T.; Seitola, T.; Mäkelä, H.M.; Hyvönen, R.; Laapas, M.; Drebs, A. Energy demand for the heating and cooling of residential houses in Finland in a changing climate. *Energy Build.* **2015**, *99*, 104–116. [CrossRef]
- 59. Eyre, N.; Baruah, P. Uncertainties in future energy demand in UK residential heating. Energy Policy 2015, 87, 641–653. [CrossRef]
- 60. Harris, S.; Weinzettel, J.; Bigano, A.; Källmén, A. Low carbon cities in 2050? GHG emissions of European cities using production-based and consumption-based emission accounting methods. *J. Clean. Prod.* **2020**, 248, 119206. [CrossRef]
- 61. Zhang, C.; Hu, M.; Sprecher, B.; Yang, X.; Zhong, X.; Li, C.; Tukker, A. Recycling potential in building energy renovation: A prospective study of the Dutch residential building stock up to 2050. *J. Clean. Prod.* **2021**, *301*, 126835. [CrossRef]
- 62. Hoxha, E.; Röck, M.; Truger, B.; Steininger, K.; Passer, A. Austrian GHG emission targets for new buildings and major renovations: An exploratory study. *IOP Conf. Ser. Earth Environ. Sci.* **2020**, *588*, 032052. [CrossRef]

Sustainability **2024**, 16, 7319 26 of 26

63. Perissi, I.; Jones, A. Investigating European Union Decarbonization Strategies: Evaluating the Pathway to Carbon Neutrality by 2050. *Sustainability* **2022**, *14*, 4728. [CrossRef]

64. Zhang, C.; Hu, M.; van der Meide, M.; Di Maio, F.; Yang, X.; Gao, X.; Li, K.; Zhao, H.; Li, C. Life cycle assessment of material footprint in recycling: A case of concrete recycling. *Waste Manag.* **2023**, *155*, 311–319. [CrossRef]

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.